

PAGE			OF			QUOTE			ORDER			Frame & Sash Colour		External	Internal	Cill		Handle (Choose one of the below)							
Company Name:						Company Ref.						White 9016 Gloss				No Cill			ProLinea			Harbour			
Company Telephone:						Company Email:						Anthracite Grey 7016 Matt				190mm Cill (Double Track Only)			White			316 Brushed Stainless			
Date Ordered:						Delivery Date Required:						Black 9005 Matt				230mm Cill (Triple Track Only)			Black			Luna Black PVD Stainless			
												Bespoke RAL Subject to minimum order qty. Price on application.							Chrome			Europa Window ^A			
Overall Dimensions						Interlock Size						Glazing						35mm Frame Extensions		Trickle Vents [‡] Specify vent quantity and positions on Configuration or in NOTES					
Width (mm)						25mm (Bonded)*						28mm Clear Tough DG						Top			PVC Vent in 35mm Frame Extender				
Height (mm)						50mm						28.8mm Laminated DG						Left			Aluminium Vent in 35mm Frame Extender				
PAS24 Spec Required				Marine Grade Required**				Supply in Kit Form				Unglazed Still tick which glazing units you will use.						Right							

DOUBLE TRACK

Configurations
(When viewed from the outside)

TRIPLE TRACK

$\overrightarrow{X}$ O	O $\overrightarrow{X}$ O	O $\overleftarrow{X}_M$ $\overrightarrow{X}$ O
O $\overleftarrow{X}$	O $\overleftarrow{X}$ O	O $\overleftarrow{X}$ $\overrightarrow{X}_M$ O
$\overrightarrow{X}_{INT}$ $\overleftarrow{X}_{EXT}$	$\overrightarrow{X}$ O O	$\overrightarrow{X}$ $\overleftarrow{X}_M$ $\overrightarrow{X}$ $\overleftarrow{X}$
$\overrightarrow{X}_{EXT}$ $\overleftarrow{X}_{INT}$	O O $\overleftarrow{X}$	$\overrightarrow{X}$ $\overleftarrow{X}$ $\overrightarrow{X}_M$ $\overleftarrow{X}$

Key: X = Slider (Arrow displays direction viewed from outside) O = Dummy INT = Internal Slider EXT = External Slider M = Master
NOTE: Overall sizes to include cill and extenders, sketch viewed from outside. Lead/Master Sliding Sash supplied on Internal Track as standard.

NOTES

Standard Spec: Reinforcement bar may need to be fitted to the Interlock (wind load dependant) – default door spec based on testing to 800pa. 3* Cylinders.
Face Drainage. Threshold only available as 42mm Standard Outer Frame. 24mm deduction for cills.

*Glazing must be bonded to 25mm Interlock, using Neutral Cure Silicone (not supplied by Listers). **Special Guarantee may apply; Harbour handles are recommended. †PVC and Aluminium vents in a 35mm Frame Extender available in sizes achieving 2500EA, 4000EA and 5000EA per vent.
^Only used for sliding windows (non-locking internal handle only, no external access, used for frame heights less than 1666mm (excl/ add on/ cill).

