

PAGE OF QUOTE ORDER

Company Name: Company Ref:

Company Telephone: Company Email:

Date Ordered: Delivery Date Required:

Profile Colour	External	Internal
White (Smooth)		
White Ash*¥		
Anth. Grey 7016		
Golden Oak		
Rosewood		
Irish Oak*		
Cream (Smooth)¥		

Profile Colour	External
Anth. Grey 7016 (Smooth)†‡	
Slate Grey 7015†‡	
Slate Grey 7015 (Smooth)†‡	
Agate Grey‡	
Black‡	
Chartwell Green*‡	
Cream White*‡	

Glazed Unglazed Handle Colour:

Ovolo Profile Chamfered Profile Ovolo Bead Chamfered Bead

Bay Location	Bay Height	Bay Cill Type	Drainage		Trans/Mullions		Glass/Panel Type (Black Warm Edge Spacer Bar as Standard)	Outer Frame		Ventilation (Specify Size)		
			Con	Face	Split	Drop		Standard 55mm	Large 75mm	Sash	Frame (75mm Only)	50mm Extender

Additional Bay Information:	
Is this a bow bay conversion? Please note for bow bay conversions supply external brick to brick opening size for backline measurement and internal size for the projection.	<input type="checkbox"/>
Reinforced Cill Required	<input type="checkbox"/>
Load Bearing Bay Jacks Required	<input type="checkbox"/>
Pole Type:	
Fixed Square Post 90°	<input type="checkbox"/>
Featured Fixed Sq. Post 90°	<input type="checkbox"/>
Variable Angle Pole 120-170°	<input type="checkbox"/>
Fixed Angle Post 135°	<input type="checkbox"/>
Fixed Angle Post 150°	<input type="checkbox"/>
Fixed Angle Post 160-170°	<input type="checkbox"/>
No Poles with Flexi Trims	<input type="checkbox"/>
No Poles, No Deductions	<input type="checkbox"/>

SKETCH & NOTES - for frame designs and if required additional bay layout details

or see frame items ____ to ____ on attached window/door order form

NOTES

- All measurements are INTERNAL.
- Backline measurements taken from inside of end frames.
- Projection measurements from inside of front frame to backline.
- Any reverse angled bays, measure & state clearly in the SKETCH & NOTES section.

A	mm
B	mm
C	mm
D	mm
E	mm
F	mm
G	mm
H	mm
I	mm
J	mm
K	mm

Standard Spec: 55mm frame, 28mm glazing, ovolo beads, white furniture, hidden drainage, fully welded, shootbolt locking, security hinges, standard transom drop 400mm

Key: D = Dummy F= Fire Hinge R = Restrictor hinge T = Toughened glass TV = Trickle vent L = Letter plate * = Ovolo Only † = Chamfered Only ‡ = External Only ¥ = Both Sides Only
NOTE: All sizes shown include cill and extensions - All viewed from outside. Sketch arrow points to hinge side.