



Timeless Flush Bay Window Order Form

Web: www.listerwindows.co.uk Tel: 0800 634 3110

PAGE <input type="text"/>	OF <input type="text"/>	QUOTE <input type="text"/>	ORDER <input type="text"/>
Company Name:		Company Ref.:	
Company Telephone:		Company Email:	
Date Ordered:		Delivery Date Required:	

Colour	External	Internal	Colour	External	Internal
White (Smooth)			Golden Oak		
White Grain			Irish Oak		
Anth. Grey 7016			Anth. Grey 7016 (Smooth)		
Rosewood			Spectral Anth. Grey 7016*		
Black			Chartwell Green†		N/A
Cream			Pebble Grey†		N/A
Agate Grey			Silver Grey†		N/A
			Slate Grey†		N/A

Glazed <input type="checkbox"/>	Unglazed <input type="checkbox"/>	Astragal Bar <input type="checkbox"/>	Rustique Profile & Bead <input checked="" type="checkbox"/>	Timberweld® (90° Square Joints) <input type="checkbox"/>	Fully Welded (45° Mitre Joints) <input type="checkbox"/>
---------------------------------	-----------------------------------	---------------------------------------	---	--	--

Bay Location	Bay Height	Bay Cill Type	Drainage		Trans/Mullions		Glass/Panel Type (Black Warm Edge Spacer Bar as Standard)	Outer Frame		Ventilation (Specify Size)		
			Con	Face	Split	Drop		Standard 56mm	Large 72mm	Sash	Frame (72mm Only)	45mm Extender

Additional Bay Information:	
Is this a bow bay conversion? Please note for bow bay conversions supply external brick to brick opening size for backline measurement and internal size for the projection.	
Reinforced Cill Required	
Load Bearing Bay Jacks Required	
Pole Type:	
Rustique Square Post 90°	
Rustique Variable Pole 120°-170°	
Tri-Pole Couplers 159°-179°	
Fast Lock Square Post 90°	
Fast Lock Fixed Angle Post 135°	
No poles, No deductions	

SKETCH & NOTES - for frame designs and if required additional bay layout details

or see frame items ____ to ____ on attached window/door order form

NOTES

- All measurements are INTERNAL.
- Backline measurements taken from inside of end frames.
- Projection measurements from inside of front frame to backline.
- Any reverse angled bays, measure & state clearly in the SKETCH & NOTES section.

A	mm
B	mm
C	mm
D	mm
E	mm
F	mm
G	mm
H	mm
I	mm
J	mm
K	mm

Standard Spec: 56mm Rustique frame, Flush Sash, dummies to all fixed, 28mm glazing, hidden drainage, black gasket, espag locking, security hinges, std transom drop 400mm

Key: D = Dummy F = Fire Hinge R = Restrictor hinge T = Toughened glass TV = Trickle vent L = Letter plate * = System10 Only † = External Only
 NOTE: All sizes shown include cill and extensions - All viewed from outside. Sketch arrow points to hinge side. Timberweld® applies to sash only, frame/transom/mullion are mechanical

